

FEATURES:

- Dynamic Element
- Omni-Directional Pickup Pattern
- Cyclac Housing with Die Cast Base
- Push-To-Talk Bar with Locking Switch or Lift-To-Talk Operation
- Heavy Duty Four Conductor Shielded Cable
- High or Low Impedance Selection



DESCRIPTION:

Dynamic microphone provides modern styling and features in a rugged Cyclac housing for industrial/commercial public address, and paging applications. Long life DPDT leaf switch provides push-to-talk (with lock capability). A Lift-to-talk switch with a bypass slide switch is also provided. The SBS-400 has a slide switch for low or high impedance applications. Common uses include restaurants, police and fire dispatch, bowling alleys and office communications.

Specifications:

ELEMENT

Dynamic

IMPEDANCE

HiZ: 40k ohms
LoZ: 400 ohms

FREQUENCY RESPONSE

50 Hz - 12 kHz

PATTERN

Omni-Directional

SWITCH

DPDT leaf

CABLE

7' 4 Conductor (2 shielded)

HOUSING AND FINISH

Molded cyclac in black with die cast base

DIMENSIONS AND WEIGHT

9.28" (23.57 cm) H x 4.35" (11.05 cm) W x 6" (15.2 cm) D
Weight: 1.5 lbs (.67 kg)

ARCHITECTS' AND ENGINEERS

The Desk Paging Microphone, Model SBS-400, shall consist of a dynamic microphone and desk stand. The frequency response shall be 50 Hz to 12 kHz with an omni-directional pattern. The impedance of the microphone shall be 400 ohm. The sensitivity of the microphone shall be -58 dB (Ref. 0 dB = 1 mw/10 microbars).

Long life DPDT leaf switch provides choice of push-to-talk (with lock capability) or lift-to-talk operation and provides a contact closure for amplifier muting if required. The push-to-talk slide bar switch shall also include a slide lock. The lift-to-talk operation can be disabled with a slide switch located under the microphone base. The cord shall be 7' (213.36 cm) in length with four conductors and two shields.

The housing shall be molded cyclac finished in black with a die cast base.

The dimensions of the microphone shall be: 9 3/8" (23.81 cm) H x 4 11/32" (11.03 cm) W x 5 27/32" (14.84 cm) D. The approximate weight shall be 23 ounces (0.37 kg).

Warranty information may be found on our website at www.valcom.com/warranty.