

# Technical Specifications

## V-1026C Bi-Directional Corridor Woodgrain Wall Speaker

- Paging, emergency alerts and tones
- One-way paging
- Utilizes standard CAT 3, 5, or 6 cable
- Excellent voice and music reproduction
- Wide sound dispersion
- Externally accessible volume control
- Electrically, acoustically matched components
- Attractive walnut finish
- Quick and easy installation
- Indoor use only



*Self-amplified one-way  
bi-directional*

### Description:

Valcom's V-1026C Bi-Directional Corridor Wall Speaker has a built-in amplifier and volume control that allows you to distribute voice paging, emergency alerts and music throughout your organization. The V-1026C is suitable for areas that need intelligible voice and background music - areas such as long hallways, classrooms, retail stores, restaurants and offices.

## SPECIFICATIONS

### SPEAKER ELEMENT

**Cone Diameter:** 8.00in (20.32cm)  
**Voice Coil Impedance:** 45 Ohms

### INPUT

**Impedance:** > 600 Ohms nominal  
**Signal Level:** -15 dBm line level

### OUTPUT

**Rating:** > 96 dB @ 4ft (1.22m)  
**Signal/Noise Ratio:** -70

### POWER REQUIREMENTS

50 mA @ -24 Vdc

### FREQUENCY RESPONSE

80 Hz to 15 kHz

### MAGNET

Cone type with 5oz (142g) ceramic magnet

### ENVIRONMENT

**Temperature:** -4 to +131°F (-20 to +55°C)  
**Humidity:** 0 to 95% non-condensing

### HOUSING AND FINISH

Baffle constructed of 0.50in (1.27cm) particle board, covered with dark with walnut vinyl with matching light brown open-weave cloth

### DIMENSIONS AND WEIGHT

10.30in H x 10.30in W x 4.20in D  
(26.16cm x 26.16cm x 10.67cm)

**Weight:** 5.60lbs (2.52kg)

**Shipping Weight:** 8.20lbs (3.69kg)

2022 Rev 7.7.18

# Technical Specifications

## ARCHITECTS AND ENGINEERS

The Bi-Directional Corridor Speaker, model V-1026C shall consist of a 45 Ohm speaker, amplifier, volume control, baffle and mounting bracket.

The V-1026C Bi-Directional Corridor Speaker housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 15 kHz.

The V-1026C Bi-Directional Corridor Speaker element shall be cone type with 5oz (142g) ceramic magnet. Diameter of speaker cone shall be 8.00in (20.32cm). Voice coil diameter shall be 0.75in (1.91cm). Voice coil impedance shall be 45 Ohm.

The V-1026C Bi-Directional Corridor Speaker amplifier shall have a frequency response of 80 Hz to 15 kHz. Distortion shall be less than 1.5% at rated output of 1-Watt RMS. Signal-to-noise ratio shall be -70 dB. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply.

The V-1026C Bi-Directional Corridor Speaker operating current shall be 50 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C).

The V-1026C Bi-Directional Corridor Speaker baffle shall be constructed of 0.50in (1.27cm) particle board covered with dark walnut vinyl with light brown open weave cloth grille. A screwdriver adjustable volume control shall be provided on the unit. This volume control shall be externally accessible, making it possible to adjust volume level of speaker without removal of unit. The V-1026C shall be suitable for indoor applications.

The maximum dimensions shall be: 10.30in H x 10.30in W x 4.20in D (26.16cm x 26.16cm x 10.67cm). Weight shall be approximately: 5.60lbs (2.52kg).

Warranty information may be found on our website at [www.valcom.com/warranty](http://www.valcom.com/warranty).