

Technical Specifications

V-5580041C Analog Strobe

- Produces 115 candela of brilliancy
- Covers 70 foot by 70 foot of area
- Fits into a standard 2x2 electrical box (included)
- Can be activated by applying power, dry contact closure or 70 Volt speaker voltage
- Flash rate is designed to comply with ADA
- Power supply included



ADA Compliant

Description:

The V-5580041C Analog Strobe allow you to provide a visual notification to individuals within your organization. The V-5580041C is ideal for corporate applications, educational institutions, entertainment complexes, industrial facilities, government buildings, healthcare facilities, transportation terminals or anywhere the need for critical alerts/public address exists. V-9955 Auxiliary Relay Unit is used in conjunction with the V-5580041C for strobe activation, door and camera control. The Relay Unit is expandable to 6 relays by adding an expansion board.

SPECIFICATIONS

VISIBILITY

Typical coverage of 4900 sq. ft. @ 80 inch mounting height

POWER REQUIREMENTS

Power supply operating voltage input: 110 Vac

Strobe minimum operating voltage: 18 Vdc

Strobe maximum operating voltage: 30 Vdc

Current draw: 210 mA

ENVIRONMENT

Indoor use

HOUSING AND FINISH

Lens color: Amber

Faceplate cover: Ivory

Metal mounting box: Silver

DIMENSIONS AND WEIGHT

5.63in H x 4.63in W x 4.50in D
(14.29cm x 11.75cm x 11.43cm)

Weight: 1.40lbs (0.64kg)

Shipping Weight: 4.00lbs (1.80kg)

ACCESSORY

V-9955 Auxiliary Relay Units

ARCHITECTS AND ENGINEERS

The Analog Strobe, model V-5580041C, shall consist of a lens, face cover, mounting box, and power supply. The V-5580041C shall be ADA compliant with a 115 Candella rating.

The V-5580041C Analog Strobe shall have a power supply operating voltage input of 110 Vac. The V-5580041C shall have a strobe minimum operating voltage of 18 Vdc and a maximum operating voltage of 30 Vdc. The V-5580041C current draw shall be 210 mA.

The V-5580041C Analog Strobe shall be constructed of an ivory

color faceplate cover, amber lens and a silver metal mounting box. The V-5580041C shall be suitable for indoor applications.

Maximum microphone dimensions shall be: 1.75in D x 4.63in L
5.63in H x 4.63in W x 4.50in D (14.29cm x 11.75cm x 11.43cm)
Weight shall be approximately: 1.40lbs (0.64kg).

Warranty information may be found on our website at www.valcom.com/warranty.

2022 Rev. 1.8.4