

Technical Specifications

V-9912P-12/ V-9912M-10 Mounting Ring

V-9912P-12

- Provides a solid mounting structure
- Sturdy plastic design
- 12 per pack

V-9912M-10

- Provides a solid mounting structure
- Sturdy metal design
- Steel ring is galvanized to inhibit rust
- 10 per pack



*Provides solid mounting structure
8.00in ceiling speakers*

Description:

The V-9912P-12 Mounting Ring is designed for quick and easy installation and securely mounts 8-inch round ceiling speakers in retrofit sheetrock ceilings.

The V-9912M-10 Mounting Ring is designed for quick and easy installation and securely mounts 8-inch round ceiling speakers in new or existing sheetrock ceilings.

SPECIFICATIONS

HOUSING AND FINISH

V-9912P-12: Plastic

V-9912M-10: Metal

V-9912P-12

13.63in H x 0.50in D
(34.61cm x 1.27cm)

Weight: 0.50lb (0.23kg)

Shipping Weight: 6.80lbs (3.06kg) 12 per box

DIMENSIONS AND WEIGHT

V-9912M-10

18.50in H x 13.50in W x 0.50in D
(46.99cm x 34.29cm x 1.27cm)

Extensions, 5.25in H x 6.25in W
(13.34cm x 15.88cm)

Weight: 1.00lbs (0.45kg)

Shipping Weight: 12.60lbs (5.67kg) 10 per box

ARCHITECTS AND ENGINEERS

The Speaker Mounting Ring, model V-9912M-10 shall be constructed of lightweight metal. The V-9912M-10 shall be compatible for use in new or existing construction sheetrock/drywall ceilings. The V-9912M-10 shall have four (4) extruded holes for #8-32 screws. The V-9912M-10 shall have 11.25in diameter bolt circle and shall include slotted wings for attachment to 16.00in wide joists. The V-9912M-10 shall include 2 extender brackets for attachment to 24.00in wide joists. The V-9912M-10 shall be compatible with IP and standard Valcom 8.00in flush mount ceiling speakers with round grille. The maximum dimensions shall be: 18.50in H x 13.50in W x 0.50in D (46.99cm x 34.29cm x 1.27cm). The extensions, maximum dimensions shall be 5.25in H x 6.25in W (13.34cm x 15.88cm). Weight shall be approximately: 1.00lbs (0.45kg).

The Speaker Mounting Ring, model V-9912P-12, shall be constructed of plastic. The V-9912P-12 shall be compatible for use in post-construction retrofit gypsum (sheetrock) ceilings. The V-9912P-12 shall be conveniently installed by cutting a 12 inch (305mm) diameter hole in the ceiling and attaching four J-nuts to the inside diameter of the ring. The V-9912P-12 shall be compatible with IP and standard Valcom 8.00in flush mount ceiling speakers with round grille. The maximum dimensions shall be: 13.63in H x 0.50in D (34.61cm x 1.27cm). Weight shall be approximately: 0.50lbs (0.23kg).

Warranty information may be found on our website at www.valcom.com/warranty.

2022 Rev. 1.8.9