

Technical Specifications

VIP-142-IC InformaCast® Compliant IP Paging Horn

- SIP & Multicast enabled
- Power over Ethernet
- Remote management & monitoring
- Polycarbonate plastic housing
- Omni-directional mounting base
- Built-in microphone
- Indoor/outdoor use



*High power talkback
built-in microphone*

Description:

The VIP-142-IC InformaCast Compliant High Power IP Talkback Paging Horn is a high-efficiency horn that supports multiple audio and control protocols. All notifications are delivered via a PoE enabled IP network. The VIP-142-IC is set up with a separate microphone that facilitates full duplex talkback communication. The high-impact polycarbonate construction resists the deteriorating effects of outdoor elements.

SPECIFICATIONS

FREQUENCY RESPONSE

350 Hz to 7 kHz

POWER

IEEE 802.3af (PoE) Class 3

IEEE 802.3at (PoE+) Class 4

DISPERSION

120° Horizontal and 90° Vertical

AUDIO CODECS

G.722, G.711 (uLaw, aLaw)

SOUND PRESSURE LEVEL

119 dBA @ 1 m w/1 kHz sine wave

MOUNTING

Wall, surface, I-beam

HOUSING AND FINISH

Polycarbonate plastic

ENVIRONMENT

Temperature: -4 to 122 °F (-20 to +55° C)

Humidity: 0 to 95% non-condensing

DIMENSIONS AND WEIGHT

11.75in H x 10.00in W x 11.00in D
(29.80cm x 25.40cm x 27.90cm)

Weight: 4.30lbs (1.95kg)

Shipping Weight: 8.00lbs (3.60kg)

2024 Rev. 1.9.2.7

Technical Specifications

ARCHITECTS AND ENGINEERS

The InformaCast Compliant High Power IP Talkback Paging Horn, model VIP-142-IC, shall support multiple audio and control protocols, delivered via a PoE enabled IP network. A separate microphone shall facilitate full-duplex talkback communication.

Power shall be provided to the VIP-142-IC via an Ethernet switch providing Power over Ethernet (PoE) meeting the 802.3af specification or PoE+ meeting the 802.3at specification.

Setup of the VIP-142-IC shall automatically acquire an IP address (using DHCP) and connect to the InformaCast server when connected to the network and powered up..

The VIP-142-IC High Power IP Talkback Paging Horn shall be

constructed of polycarbonate plastic. The VIP-142 shall be suitable for indoor and outdoor applications.

The VIP-1142-IC, High Power IP Talkback Paging Horn, base shall be mounted to a single gang or double-gang electrical box, directly to surface (wall) or clamped to a structural I-beam. A "C" clamp shall be included for "I" Beam mounting. The VIP-142-IC Horn shall be suitable for indoor or outdoor applications.

Maximum dimensions shall be: 11.75in H x 10.00in W x 11.00in D (29.80cm x 25.40cm x 27.90cm) Weight shall be approximately: 4.30lbs (1.95kg).

Warranty information may be found on our website at www.valcom.com/warranty.