

MODEL

V-DW11025B 2.5" Wireless Digital Clock, 110V
V-DW11040B 4.0" Wireless Digital Clock, 110V



FEATURES:

- Receives and Transmits the Signal Once A Minute
- Internal Antenna
- Each Clock Acts as A Repeater
- 915–928mhz Frequency–Hopping Technology
- Immediate Correction for Time Change
- Microprocessor Based Clock
- Clocks Will Not Deviate From Each Other
- Available In 2.5" Display And 4.0" Display
- 12- Or 24-Hour Format
- Two (2) Levels of Adjustable Brightness
- Loss of Communication Alert
- Bright LED Display
- Red Bezel
- No Battery Backup Required
- Dynamic Range for Input Voltages
- 78 - 130 VAC
- Compatible with The Valcom Wireless Analog Clocks
- Designed to Work in Conjunction with The Valcom V-WMC
- Plug in Molex Connectors
- UL and cUL Listed
- FCC Compliant, FCC Part 15 Section 15,247

DESCRIPTION:

Valcom's wireless digital clocks are available with either 2.5" high characters or 4.0" high characters in a four (4) digit display. The wireless digital clocks are slave clocks designed to work in conjunction with the Valcom Wireless Master Clock (part number V-WMCA).

The innovative 915–928 MHz frequency–hopping technology allows for a better and clearer signal even if there is interference in one of the frequencies. Not only can each clock receive the wireless signal, it also transmits the signal. The digital wireless clocks are designed to automatically work together without causing interference with each other. In fact, a large number of clocks in a specific area would increase the quality of the signal to each unit. The wireless digital clock is based on our high efficiency, bright LED display. The clocks correct immediately upon receipt of the wireless signal. The wireless digital clock features many options including 12- or 24-hour format, as well as two (2) brightness settings. The wireless digital clocks can be mounted in a surface or double mount housing. The wireless digital clock also features LEDs on the board to show if the clock is receiving data, making it easier to maintain and install. The unique, specially molded bezel gives a smooth, clean look with no visible external screws.

The Valcom wireless digital clock is FCC compliant, part 15, section 15,247.

Specifications

INPUT SENSITIVITY

-103 dBm

VOLTAGE INPUT

2.5" Clock: 78 – 130 VAC

4.0" Clock: 85 – 135 VAC

AVERAGE CURRENT CONSUMPTION

Battery – 5 years (normal mode)**

Battery – 8 years (economy mode)**

20 mA @ 24VDC

15 mA @ 110VAC

SIGNAL INPUT

Valcom Wireless Communication

SIGNAL OUTPUT

Valcom Wireless Communication

POWER OUTPUT

8 dBm (6mW)

AVERAGE CURRENT CONSUMPTION

2.5 Clock: (Max Brightness) 30 mA @ 110 VAC

4.0 Clock: 45 mA @ 110 VAC

OPERATING FREQUENCY

915 – 928 MHz frequency-hopping technology

COMPLIANCE

UL, cUL, and FCC approved, FCC part 15 Section 15,247

DISPLAY SIZE/COLOR

2.5" and 4.0" Vibrant Red characters

VISIBILITY

2.5" Clock: 100 feet

4.0" Clock: 250 feet

DISPLAY

12-hour or 24-hour format

BRIGHTNESS

2 levels, adjustable

BEZEL COLOR

Red

OPERATING TEMPERATURE

Temperature: 32 to 130°F (0 to 45°C)

Storage: (-15° to 75° C)

DIMENSIONS AND WEIGHT

2.5" clock: 7.5" L x 11.375" W x 4.25" D

4.0" clock: 9.75" L x 14.25" W x 4.25" D

Weight: 2.5" – 2 lbs (0.90 kg)

4.0" – 3.5 lbs (1.58 kg)

POWER KIT INCLUDES

1 - 5 pin power harness

4 - 6-32 x 1/2 machine screw

1 - 6-32 hex nut

1 - tooth lock washer

1 - grounding wire, loop end

MOUNTING

Surface and double mount

ARCHITECTS' AND ENGINEERS

The clock shall be a Valcom wireless digital clock and shall have either a full 2.5" or 4.0" high efficiency LED numeral display.

The clock will operate as a wireless digital slave clock. The clock shall receive signals from other clocks in the surrounding area or from the V-WMCA. The clock shall receive and transmit with 915–928MHz frequency–hopping technology. The clocks will be capable of transmitting and receiving the time without interfering with each other. The clock shall have data LEDs on the board to display the receiving of data. It shall have a 12- or 24-hour display format. The clock will have two (2) levels of adjustable brightness and will feature immediate correction for time changes. The digital clock shall be capable of being installed either surface or double mount. When the input is lost, the colon on the display of the clock shall flash.

The clock shall have a red bezel with a smooth surface. No external screws shall be visible on the bezel or clock housing. The clock shall be FCC compliant, part 15 Section 15,247.

Warranty information may be found on our website at www.valcom.com/warranty.