

Ensure An Attractive And Effective Solution For Every Environment: Offices, Meeting Rooms, Gymnasiums, Warehouses, Hallways Or Outdoor Areas.

- PoE (802.3af) - No Local Power Required
- 2.5" Characters - 5 Character Display
- Clock Updates from Any NTP Source
- Red LED's - Other LED Colors On Request
- Needs Only One Ethernet Port Connection
- Output Level 103 db/1Meter
- AUX Output Supports Valcom Amplified Speakers
- Optional Wall Volume Controls Available
- Mounting Backboxes Available
- Valcom offers a line of stand alone IP PoE clocks, visit www.valcomclocks.com



Backbox Selection Chart

IP SPEAKER/CLOCKS		One-Way or Talkback Programmable	Backbox Type
A.	IP Speaker Faceplate Unit w/ Digital Clock White	VIP-429A-D	22, 23, 24
B.	IP Speaker Surface Mount w/ Digital Clock Gray w/Black Grille	VIP-431A-DS	N/A
C.	IP Speaker Faceplate Unit w/ Digital Clock Gray w/Black Grille	VIP-431A-DF	19

Type	Part No.	Mount Style	Dimensions
19	VB-R19	Recessed	19.25"H x 10.75"W x 3.75"D Grille Hole Dimns.: 10.00" x 18.50"
20	VB-S20	Surface	20.18"H x 14.27"W x 2.78"D Grille Hole Dimns.: 10.50" x 18.50"
21	VB-A21	Angled <i>Only works with Digital Clocks.</i>	19.88"H x 14.27"W x 5.50"D ¹ x 2.71"D ² Grille Hole Dimns.: 10.50" x 18.50"
22	VB-R22	Recessed	13.25"H x 11.25"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
23	VB-S23	Surface	14.63"H x 13.13"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
24	VB-A24	Angled	14.41"H x 13.13"W x 5.00"D ¹ x 3.00"D ² Grille Hole Dimns.: 10.50" x 12.50"