

Always on Duty.™

Single button press provides immediate two-way connection with security personnel.

FEATURES

Sleek, Modern Design

Lightweight and Vandal-Resistant

Built-In Lightning Protection

Enhanced Reliability in Storm Prone Regions

1 or 2 Call Buttons

Emergency, Information, Directions, etc.

High-Intensity Blue LED Light

Always On and Flashes During Emergency Calls

FUNCTIONS

Caller ID

For Precise Location

Hands-Free Intercom Operation

When the Called Party Answers, Instant Hands-Free Communication is Enabled

Optional 360-Degree Speaker Array

One-Way High-Level Audio Broadcasting for Emergency Broadcasts

Optional IP Camera

For Emergency Viewing

Emergency Listening

Programmable Silent Activate Mode

DURABILITY

Security Type Hardware

Corrosion and Vandal-Resistant

Durable Manufacturing

Structural Grade Corrosion Proof Aluminum

Clear Dome

Durable UV-Resistant Polycarbonate Material

COMPATIBILITY

MultiCast Paging

Valcom, InformaCast®, or Syn-Apps® Protocols

Compatible with

Valcom, Cisco®, Avaya®, Mitel®, NEC®, and most other SIP-Based Systems, including Hosted or On-Premise

Easy Software

For Set-Up and Management – Free Supervision Software Available

Power

Multiple Power and Network Connectivity Options



IP Emergency HelpPoint™ Call Tower
VE9811

Options



Base Tower



Camera



360-Degree Speaker Array



Colors

LIT327

IP Emergency HelpPoint™ Call Tower Configurator VE9811

Power

PoE +

120VAC

24VDC

Tower Color

Red ■ Gray ■

Blue ■ Yellow ■

Lettering

EMERGENCY

ASSISTANCE

NONE

Lettering Color

White

Blue

Call Buttons

1st Default Button
"EMERGENCY"

2nd Optional
"CALL"

Site Name: _____

Contact Name: _____

Address: _____

City, State, ZIP: _____

Contact Phone Number: _____

Options

360-Degree Speaker Array
Compatible with Valcom, InformaCast & Syn-Apps Protocols

Camera Arm with universal mount
(Camera not included)
Camera Model: _____

(Requires AC/DC power or separate PoE + network drop)

Protocols

VALCOM/SIP

InformaCast® compatible

Syn-Apps® compatible

Communication

Ethernet

Fiber Optic Cable

Single Mode

850 nm 1300 nm

Multimode

1310 nm 1550 nm

Termination

LC SC

ST

Wireless Point-to-Point
(Wireless not included)
Wireless Model: _____

(Requires AC/DC power or separate PoE + network drop)

Customization options are available, please call Valcom. May incur additional cost and extended lead times. Information is subject to change without notice.