

# Technical Specifications

## V-1016 Wall Speaker

- Paging, emergency alerts and tones
- One-way paging
- Utilizes standard CAT 3, 5, or 6 cable
- Excellent voice and music reproduction
- Externally accessible volume control
- Electrically, acoustically matched components
- Attractive white (-W) or black (-BK) finish
- Quick and easy installation
- Indoor use only



*Self-amplified one-way*

### Description:

The V-1016 is a One-Way Angled Wall Speaker that generates high quality voice paging and emergency alerts for indoor areas. The V-1016 Wall Speaker includes a mounting bracket for quick and easy installation.

## SPECIFICATIONS

### SPEAKER ELEMENT

Cone Diameter: 8.00in (20.32cm)  
Voice Coil Impedance: 45 Ohms

### INPUT

Impedance: > 600 Ohms nominal  
Signal Level: -10 dBm line level

### OUTPUT

Rating: > 96 dB @ 4ft (1.22m)  
Signal/Noise Ratio: -70

### POWER REQUIREMENTS

50 mA @ -24 Vdc

### FREQUENCY RESPONSE

80 Hz to 16 kHz

### MAGNET

Cone type with 5oz (142g) ceramic magnet

### ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55°C)  
Humidity: 0 to 95% non-condensing

### HOUSING AND FINISH

Baffle constructed of 0.50in (1.27cm) particle board, covered with white or black vinyl with matching cloth grille.

### DIMENSIONS AND WEIGHT

9.70in H x 11.50in W x 4.00in D  
(24.64cm x 29.21cm x 10.16cm)

Weight: 4.10lbs. (1.85kg)

Shipping Weight: 6.60lbs (2.97kg)

2022 Rev 7.7.18

# Technical Specifications

## ARCHITECTS AND ENGINEERS

The Wall Speaker, model V-1016, shall consist of a 45 Ohm speaker, amplifier with > 600 Ohm input impedance, volume control, angled baffle and mounting bracket. The V-1016 Wall Speaker shall be available in black (-BK) or white (-W).

The V-1016 Wall Speaker housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 10 kHz.

The V-1016 Wall Speaker element shall be cone type with 5oz (142g) ceramic magnet. Diameter of speaker cone shall be 8.00in (20.32cm). Voice coil diameter shall be 0.75in (1.91cm). Voice coil impedance shall be 45 Ohm.

The V-1016 Wall Speaker amplifier shall have a frequency response of 80 Hz to 15 kHz. Amplifier audio input impedance shall be > 600 Ohm. Amplifier audio input shall be -10 dBm line level. Distortion shall be less than 1.5% at rated output of 1-Watt RMS. Signal-to-noise ratio shall be -70 dB. The amplifier shall operate on a -24 Vdc

nominal, positive ground power supply.

The V-1016 Wall Speaker operating current shall be 50 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C).

The V-1016 Wall Speaker baffle shall be constructed of 0.50in (1.27cm) particle board covered with white or black vinyl with matching white or black cloth grille. A screwdriver adjustable volume control shall be provided on the unit. This volume control shall be externally accessible, making it possible to adjust volume level of speaker without removal of unit. The V-1016 shall be suitable for indoor applications.

The maximum dimensions shall be: 19.70in H x 11.50in W x 4.00in D (24.64cm x 29.21cm x 10.16cm). Weight shall be approximately: 4.10lbs (1.85kg).

Warranty information may be found on our website at [www.valcom.com/warranty](http://www.valcom.com/warranty).