# **Technical Specifications**

# V-400 Dynamic Desk Paging Microphone

- Public address/emergency live voice
- Omni-directional
- Rubber feet to reduce noise
- Push-to-talk with locking bar or Lift-to-talk mode
- Reduces background noise
- Indoor use



# Description:

The V-400 Desktop Paging Microphone features modern styling and a rugged construction. The V-400 is ideal for restaurants, retail stores, bowling alleys, offices, transportation terminals and dispatch centers..

# **SPECIFICATIONS**

#### **ELEMENT**

Dynamic

#### **OUTPUT**

Output Level: -58 dB (Ref. 0 dB = 1 mw/10 Micro-

bars)

Output Impedance: Lo Z, 400 Ohms

#### FREQUENCY RESPONSE

50 Hz - 12 kHz

#### **PATTERN**

Omni-directional

## **SWITCH**

**DPDT** leaf

#### **CABLE**

7ft 4 Conductor (2 shielded)

#### **HOUSING AND FINISH**

Molded cycolac in black with die cast base

#### **DIMENSIONS AND WEIGHT**

9.40in H x 4.00in W x 6.00in D (23.88cm x 10.16cm x 15.24cm)

Weight: 1.40lbs (0.64kg)

Shipping Weight: 3.70lbs (1.67kg)

### **ARCHITECTS AND ENGINEERS**

The Desk Paging Microphone, model V-400, shall consist of a dynamic microphone, desk stand, a push-to-talk push bar with lock and a 7ft cord.

The V-400 Paging Microphone shall have a frequency response of 50 Hz to 12 kHz with an omni-directional pattern. The impedance of the V-400 microphone shall be 400 Ohm. The sensitivity of the microphone shall be -58 dB (Ref. 0 dB = 1 mw/10 microbars).

The V-400 Paging Microphone shall include a long life DPDT leaf switch that provides a choice of push-to-talk (with lock capability) or lift-to-talk operation and a contact closure for amplifier muting, if required. The push-to-talk slide bar switch shall also include a slide lock. The lift-to-talk operation can be disabled with a slide switch

located under the microphone base. The V-400 Paging Microphone cord shall be 7ft (213.36cm) in length with four conductors and two shields.

The V-400 Paging Microphone shall be constructed of molded cycolac and finished in black with a die cast base. The V-400 shall be suitable for indoor applications.

Maximum dimensions shall be: 9.40in H x 4.00in W x 6.00in D (23.88cm x 10.16cm x 15.24cm). Weight shall be approximately: 1.40lbs (0.64kg).

Warranty information may be found on our website at www.valcom.com/warranty.

2022 Rev. 7.8.4

