

**TECHNICAL SPECIFICATION
TALKBACK WALL SPEAKER
MODEL VC-1062A**



FEATURES:

- Built-In Volume Control
- Excellent for Voice and Music Reproduction
- Wide Sound Dispersion
- Electrically, Acoustically Matched Parts
- Attractive Walnut Finish



DESCRIPTION:

Wall surface mounted speaker assembly complete with 45-ohm speaker, sloped baffle.

Specifications

SPEAKER ELEMENT

Cone Diameter: 8.0" (20.32 cm)
Voice Coil Impedance: 45 Ohm

FREQUENCY RESPONSE:

60 Hz to 12 kHz

POWER RATING:

12-Watts

ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55°C)
Humidity: 0-95% Non-Condensing

HOUSING AND FINISH

Baffle constructed of .5" (1.27 cm) particle board, covered with walnut vinyl with light brown open weave cloth grille.

DIMENSIONS AND WEIGHT

10.6 "H x 9.7 "W x 5.2 "D (26.924 cm x 24.638 cm x 13.208 cm)
Weight: 4.4 lbs (1.98 kg) **Shipping Weight:** 5.3 lbs (2.385 kg)

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model VC-1062A shall consist of a speaker, volume control and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 60 Hz to 12 kHz.

The speaker shall be 8" (20.32 cm) in diameter and have a ceramic magnet weighing 5 ounces. The impedance of the speaker shall be 45 Ohm. The voice coil shall be .75" (1.91 cm) in diameter. Voice coil impedance shall be 45-ohm. Operating temperature shall be -40 to + 131°F (-20 to + 55°C).

The baffle shall be constructed of .5" (1.27 cm) particle board covered with simulated walnut vinyl and have a light brown open-weave grille cloth. Maximum dimensions of the housing shall be 10.6 "H x 9.7 "W x 5.2 "D (26.924 cm x 24.638 cm x 13.208 cm). Approximate weight is 4.4 lbs (1.98 kg).

Warranty information may be found on our website at www.valcom.com/warranty.