

TECHNICAL SPECIFICATION
12VDC/500mA POWER SUPPLY
MODEL VP-412A



FEATURES:

- Used For V-2952 FM Tuner and V-9970 Station Adapter Only
- 12 Volt DC Unfiltered Power Supply
- Input Thermal Fuse Protected
- Floating Output
- Receptacle Mount



DESCRIPTION:

Receptacle mount, 12 Vdc -400 mA, class 2, unfiltered power supply. Used for V-2952 FM Tuner and V-9970 Station Adapter only.

Specifications

INPUT

Voltage/Frequency: 105-120 Vac, 60 Hz
Power: 10 Watts
BTU/Hr: 35
Connection: 2 Prong AC Plug

OUTPUT

Voltage: 12 Vdc Unregulated, Unfiltered, Floating
Current: 400 mA
Connections: 2.5 mm Barrel Connector

REGULATORY

UL, cUL Listed

ENVIRONMENT

Temperature: 32 to 12 °F (0 to 50°C)
Humidity: 10-85% Non-condensing

DIMENSIONS AND WEIGHT

2.6 "H x 2 "W x 2.3 "D (6.604 cm x 5.08 cm x 5.842 cm)
Weight: 0.5 lbs 0.23 kg **Shipping Weight:** 0.7 lbs (0.315 kg)

MOUNTING

Receptacle

ARCHITECTS' AND ENGINEERS

The 12 Vdc, 400 mA Power Supply, Model VP-412A, shall be receptacle mount, class 2, unfiltered power supply. The unit shall be solid state and provide thermal fuse protection. Screw terminals shall be provided for output connections. The unit shall be UL and cUL Listed.

The power supply shall provide a floating 12 Vdc output. Output connection shall be a 2.5 mm barrel plug.

Input voltage shall be 105 - 120 Vac, 60 Hz, 10 watts maximum.

Operating temperature shall be 32 to 122°F (0 to 50°C). Operating humidity shall be 0 to 85% non-condensing.

The power supply shall be housed in a black, high impact ABS plastic case. The case shall be sealed. Maximum dimensions shall be 2.6 "H x 2 "W x 2.3 "D (6.604 cm x 5.08 cm x 5.842 cm). Weight shall 0.5 lbs (0.23 kg).

Warranty information may be found on our website at www.valcom.com/warranty.