

Technical Specifications

V-PEHRFS-SS | Surface Mount Enclosure

- For Valcom FlexHorn™ loudspeakers
- 316L stainless steel grille with brushed finish
- 316L stainless steel backbox with powder-coated finish
- Surface mount design suitable for outdoor use
- Universal junction box pattern and four direct wall mounting holes
- 3/4 in or 1 in electrical knockout; one-way security screws



V-PEHRFS-SS

Description:

The V-PEHRFS-SS is a surface mount enclosure designed for Valcom FlexHorn™ loudspeakers. Its stainless-steel grille and backbox are suitable for outdoor use. Compatible loudspeakers are sold separately.

SPECIFICATIONS

COMPATIBILITY

Valcom FlexHorn™ loudspeakers; sold separately.

MOUNTING

Surface mount to a compatible junction box, or directly to a suitable wall or structure using the four corner holes and installer-supplied corrosion-resistant fasteners. Wiring enters through the rear junction box opening or 3/4 in or 1 in electrical knockout; use an approved fitting at the knockout. Install the loudspeaker with supplied 8-32 KEPS nuts and secure the grille with supplied one-way security screws.

ENVIRONMENT

Suitable for outdoor use. Field wiring shall comply with applicable electrical codes.

HOUSING AND FINISH

316L stainless steel grille, brushed finish; 316L stainless steel backbox, powder-coated finish.

DIMENSIONS AND WEIGHT

10.00 × 12.25 × 3.94 in
(25.40 × 31.12 × 10.01 cm)
Weight: 7.40 lb (3.36 kg)

The surface mount enclosure for Valcom FlexHorn™ loudspeakers, model V-PEHRFS-SS, shall be suitable for outdoor use and compatible with the Valcom FlexHorn™ loudspeakers. Loudspeakers shall be sold separately.

The enclosure shall have a brush finish 316L stainless steel grille and a powder-coated 316L stainless steel backbox. The backbox shall have a universal junction box mounting pattern, four direct wall mounting holes, rear wire entry and a 3/4 in or 1 in electrical knockout. The loudspeaker shall mount with

supplied 8-32 KEPS nuts, and the grille shall fasten with supplied one-way security screws. Direct wall mounting fasteners shall be installer supplied and corrosion resistant.

The dimensions shall be 10.00 × 12.25 × 3.94 in (25.40 × 31.12 × 10.01 cm). Weight shall be approximately 7.40 lb (3.36 kg).

Warranty information may be found on our website at www.valcom.com/warranty.

V-PEHRFS-SS